



## **ALL IN ONE**

### **ESU + VESSEL SEALING SYSTEM + ARGON PLASMA COAGULATION**

The line of HF Electrosurgical Units (ESU) equipped with Argon Plasma Coagulation and Vessel Sealing System is designed as a state-of-the-art product to meet the needs of modern surgery.

The variety of available operating modes enables versatile applications for Open surgery and MIS (Minimally Invasive Surgery) include Gastroenterology, Transplantation, ENT, Urology, Bronchoscopy, Orthopedic, Cardiac Surgery, Plastic Surgery, Colon-proctology, Oncology and other Laparoscopic surgeries.

# ICONIC-IS410S

## FEATURES:

- Argon Plasma Coagulation (Continuous Output)
- Argon Plasma Coagulation (Pulsed Output)
- Argon Cut
- Vessel Sealing (Seal 1) – Permanent sealing up to 7mm
- Vessel Sealing (Seal 2) – Permanent sealing up to 7mm
- Bipolar Cut
- Bipolar Coagulation (Auto-Start Bipolar & Manual Bipolar)
- Monopolar Cut (Pure)
- Monopolar Cut (Blend1)
- Monopolar Cut (Blend2)
- Monopolar Cut (Blend3)
- Monopolar Coagulation (Swift)
- Monopolar Coagulation (Forced)
- Monopolar Coagulation (Spray)
- Monopolar Coagulation (Soft)
- TUR Mode



- Automatic Self Checking (Spotting the system's internal problems)
- Permanent HF Leakage current control
- Auto Stop Mode for Optimum tissue Coagulation (Preventing tissue Carbonization)
- Utilizing a microprocessor system to control the current in vessel sealing, based on measuring the impedance of the tissue
- Permits two surgeons to coagulate at the same time independently in Spray Mode
- Connect two Monopolar & Bipolar foot switching devices independently
- 75 Programmable memory locations

Main Voltage: 220Vac + 10%, 50Hz or 110Vac + 10%, 50~60Hz  
Maximum Power Consumption: 800V.A  
Protection Class: Class I  
Type of Output: CF  
Weight: 8 kg  
Dimensions (W.H.D): 40 x 17 x 44 cm

# ICONIC-IS410

## FEATURES:

- Argon Plasma Coagulation (Continuous Output)
- Argon Plasma Coagulation (Pulsed Output)
- Argon Cut
- Bipolar Cut
- Bipolar Coagulation (Auto-Start Bipolar & Manual Bipolar)
- Monopolar Cut (Pure)
- Monopolar Cut (Blend1)
- Monopolar Cut (Blend2)
- Monopolar Cut (Blend3)
- Monopolar Coagulation (Swift)
- Monopolar Coagulation (Forced)
- Monopolar Coagulation (Spray)
- Monopolar Coagulation (Soft)
- TUR Mode



- Automatic Self Checking (Spotting the system's internal problems)
- Permanent HF Leakage current control
- Auto Stop Mode for Optimum tissue Coagulation (Preventing tissue Carbonization)
- Permits two surgeons to coagulate at the same time independently in Spray Mode
- Connect two Monopolar & Bipolar foot switching devices independently
- 75 Programmable memory locations

Main Voltage: 220Vac + 10%, 50Hz or 110Vac + 10%, 50~60Hz  
Maximum Power Consumption: 800V.A  
Protection Class: Class I  
Type of Output: CF  
Weight: 8 kg  
Dimensions (W.H.D): 40 x 17 x 44 cm







## **Trionara Technologies AB**

Trionara Technologies AB, Address: Laxfiskevägen 6, 433 38 Partille - Sweden  
Website: [www.Trionara.com](http://www.Trionara.com)  
Tel: +46-31-135514

E-Mail: [info@trionara.com](mailto:info@trionara.com)  
Fax: +46-31-7777770